

# KPT-SPD360FHEV



### Optional Mounts



## Introduction

The Vandal Resistant KPT-SPD360FHEV is an Outdoor SPEED DOME PTZ CAMERA which integrates a Sony 36x ExView Zoom Block.

This unit can monitor the target area efficiently with the PTZ control in all weather conditions.

## Special Features

- ⊙ Programmable AE(D/N, White Balance, Shutter Speed etc) per Preset
- ⊙ Optical 36x / Digital 12x Zoom / 520 TVL / 0.01 Lux (ICR)
- ⊙ Mechanical Day / Night (ICR)
- ⊙ Vandal Proof / Weather Resistant (IP66) / Built-in Fan & Heater
- ⊙ Standard Wall Mount /Optional Pendant/Pole/Corner Mount

Model	KPT-SPD360FHEV	
Signal Format	NTSC	
Camera	Device	1/4" Sony EXview HAD CCD
	Total Pixels	410K Pixels [811(H) x 508(V)]
	Resolution	520 TV Lines
	MIN. Illuminance	1 Lux (Day) 0.01 Lux (Night)
	Focus	Auto / Manual
	Iris	Auto
	BLC	On / Off
	Flickerless	FL On / Off
	Zoom	36 X Optical Zoom and 12 X Digital Zoom
	White Balance	Auto / Manual / Indoor / Outdoor
	Focal Length	F1.6 ~ 4.5 f=3.4 ~ 122.4mm
	Day & Night	Day / Night / Auto (ICR)
	Pan/Tilt	Range
Pan/Tilt Speed		Manual : 0.05° ~ 150/sec (Zoom Proportional)
		Preset : 360° /sec Swing : ~ 60° /sec (Zoom Proportional)
Preset		128 Presets / Programmable AE per Preset
Privacy Zone		8 Zones
Pattern		4 Patterns (MAX. 1 Minute Each)
Swing		8 Swings
Group	8 Groups ( MAX. 20 Entries)	
General	Sensor In/Out	4 Input / 2 Output
	Other	Auto Flip / Auto Parking
	Communication	RS-485
	Power	AC 24V / 1.5 A (Without Fan & Heater) AC 24V / 2A (With Fan & Heater)
	Dimension	252(φ) x 319(H)mm
	Operating Temp.	-30° C ~ 50° C / -22° F ~ 122° F

Specifications may change without prior notice or liability



**KT&C USA, Inc.**  
 3240 Wilshire Blvd. Suite 501  
 Los Angeles, CA 90010  
 Tel 213-381-0061 Fax 213-381-0061  
 sales@ktncusa.com / www.ktncusa.com