

TD4114IP Indoor Network Dome with Audio Capability



2.5 - 6.0mm
VARI-FOCAL
LENS

2 WAY
AUDIO

4X DIGITAL
ZOOM

Key Features & Benefits

- Simultaneous MPEG4 and MJPEG output over the network makes high quality video viewable by standard web-browsers or through PC software, at the same time that their NTSC video outputs are sent to an analog CCTV system for display or recording.
- Full day / night operation, low illumination requirements and removable IR cut filters ensure that images will be more easily identified, even under low light conditions.
- MPEG4 or MJPEG formats permit the user to adjust frame rate up to 30fps and image size/quality up to full D1 to meet a wide variety of network conditions or application requirements.
- Audio capability permits clear 2-way voice communication.
- Distance learning or A/V applications where synchronized, high quality audio is needed can be handled with minimal integration.
- Built-in motion detection sends alarm outputs to alert security personnel.
- IP filtering assures site security by restricting access to authorized users.
- Up to 50 users of MJPEG or 3 users of MPEG4 can have simultaneous access.
- Captures images at time of alarm entry. Transfers to an FTP server for later viewing.
- 4x digital zoom and 2.4x Vari-focal auto iris lens
- Minimum illumination required: 0.5lx (color), 0.05lx (B&W)

SPECIFICATIONS

TD4114IP	
CAMERA	
TV System	NTSC
Image Pick Up device	1/3" CCD
Effective picture element	768 x 494
Sync. System	Internal
Min. Illumination	Color: 0.5 lx (30 IRE) B&W: 0.05 lx (30 IRE)
White balance	AUTO/one-push/Manual/ Indoor mode/Outdoor mode/ Flourescent lamp mode
Day & Night	Yes
IR illumination	No
Back light compensation	On / Off
Wide dynamic range	No
Lens type	2.4X Vari-focal auto iris lens
Focal length	f = 2.5 - 6.0 mm
F number	F1.3 - 1.9
Digital zoom	4X
Other functions	Motion Detection
INTERFACE	
Analog video output	BNC x1
Ethernet	10 Base-T / 100 Base-TX (RJ-45)
External control terminal	Alarm I/O (6P)
Audio input	3.5mm Mini jack
Audio output	RCA Pin jack
NETWORK	
Compression format	MJPEG/MPEG4 simultaneous output
Protocol	IP, ARP, ICMP, TCP, UDP, HTTP, FTP, SMTP
Image size	D1 (704 x 480), SIF (352 x 240) QQVGA (160 x 120)
Frame rate	MJPEG: Max 30 fps (352 x 240), MPEG4: Max 30 fps (704 x 480)
Simultaneous client access	JPEG: 50 clients / MPEG4: 3 clients
SYSTEM REQUIREMENTS	
Operation system	Microsoft Windows 2000 / XP
Browser	Microsoft Internet Explorer 6.0 or later (Sun JAVA2SE Ver. 1.5.0 or later)
GENERAL	
Power source	DC12V
Power consumption	7 W
Dimensions	5.75 (D) x 5.24 (H) inches
Weight	Approx 2.2 lbs (1000 g)
Operating temperature	14 - 122°F (-10 -50°C)
Supplied accessories	AC adapter, Relay cable, Ceiling mounts, CD (Viewer, manual)
Options	Smoke Dome Cover

Specifications are subject to change without notice.
Windows and Internet Explorer are Trademarks of Microsoft Corporation.
Sun JAVA is Trademark of Sun Microsystems.



ELMO USA Corp.
Tel: 516-501-1400 • www.elmousa.com
ELMO Canada Corp.
Tel: 905-453-7880 • www.elmocanada.com