

15" LCD Professional Monitor

Model No. ; 15RTC



www.orionimages.com



■ World Leading Active Matrix TFT-LCD Panel

Truly flat LCD screen delivers razor sharp images

■ Hi Performance Image Processing Circuit

3D comb filter and deinterlace function realize perfect images

■ Real Industrial Mechanical Design

Rigid case comes with Heavy duty metal vessel, LCD protection glass

■ Versatile terminals for Security and Industrial Solution

Multiple input and output of Video(BNC Type), Audio, S-Video and RGB

■ Public View Monitor Ready

Ready to use for Public View Monitor with DC 12V outlet and mounting hole

Video

Screen Size	15"
Resolution	1024 x 768@75Hz
Contrast Ratio	700:1
Brightness	250cd/m2
Aspect Ratio	4:3
Color Depth	16.2M
Viewing Angle(H/V)	75°/75°/75°/60° (L/R/T/B)
Pixel Pitch	0.297mm
Response Time	8ms
Scanning Frequency(Horizontal)	47.6 ~ 62KHz
(Vertical)	55 ~ 77Hz
Video System	NTSC

Audio

Built-in Speakers	Yes
Gradual Volume Increase	Yes

Terminals

RGB In (15-pin)	1
Video In(BNC Jack)	1
Video Out(BNC Jack)	1
Audio In	2
Audio Out	2
S-Video In	1
S-Video Out	1
Component In	Not Available
DVI In	Not Available
PC stereo In	1

Remote Control

Transmitter	Yes
-------------	-----

Special Features

3D comb Filter	Yes
Deinterlace Function	Yes
USB Hub	Not available
DC 12V Power Outlet	Yes
LCD Protection Glass	Yes
Rack Mountable Kit	Optional
Camera Mounting Hole	2(Upper/Bottom)
Multi-lingual Menu	English, Spanish, French, German, Italian
VESA™ Standard Compatible	Yes

Additional Information

Cabinet Dimensions	
W x H x D	TBD
Weight	9.3lbs/4.2kg
Dimensions with Packaging	
W x H x D	16.9"x14.0"x6.3"/430x356x160
Weight	12.2lbs/5.5kg
Power Consumption	35W
Power Source	AC110~230V(50/60Hz)

Cabinet

Finish	Black
Tilt Stand	Yes

Warranty

Warranty: Parts/Labor	1 Year/1 Year
MTBF (Approx.)	42K hrs.

Regulations

TUV-NRTL(same as UL), CB, FCC(B), CE-EMC(LVD)

* Specification and Design are subject to change without prior notice.