



TLM-1706 TFT LCD Monitor Preliminary Specification:

MODEL		TLM-1706
DESCRIPTION		
LCD Panel	Screen Size	17 inch (diagonal)
	Viewable size	337.9mm (H) x 270.3mm(V)
	Dot Pitch	0.264mm x 0.264mm
	View angle H/V	160(H)/160(V)
	Contrast ratio	1000:1
	Brightness	300 cd/m ²
	Resolution	1280 x 1024
	Response Time	5ms
	Display Color	16.7M
Control key define		Channel, Menu, -, +, Power
Power Supply	Input-Voltage	100~240V _{AC}
	Consumption	32W max.
Video	Input	Composite video, connector: 1 BNC S-video, connector: 1 mini-din 4 pin Level: 1.0V _{p-p} / 75Ω
	Output	1 BNC connector for CVBS loop-through output,
	OSD	Contrast, Brightness, Color, Tint, Sharpness, Display Adjust, Color Temperature, Language, OSD Adjust, Audio Control, Input Select, Reset, Exit
	System Compatibility	Scanning Frequency NTSC : 15750Hz ± 500Hz / 60Hz, PAL : 15625Hz ± 500Hz / 50Hz
Analog VGA	Input	Analog RGB: 0.707V _{p-p} / 75Ω, connector: 15 pin D-Sub
	OSD	Brightness, Contrast, Display Adjust, Color Temperature, Language, OSD Adjust, Audio Control, Input Select, Reset, Exit
	Plug & Play	DDC2B
	Power Management	VESA DPMS
	Support timing	VESA VGA / SVGA / XGA / SXGA
Audio	Input/Output	connector: 2 x RCA connector Level: 1.0V _{p-p} / 1 KHz
	Speaker	2W x 2 embedded
Mechanical	Dimension	387x402x200mm(with base), 387x338x67mm(without base)
	Weight	11.0lbs/5.0Kg (with base)
Additional benefit		Rack mountable (19" standard rack, EIA-310-D) VESA mount 100x100mm ² RoHS compliant

Note: The preliminary specification are subject to change without notice.