



1/1.8" 1.4/4.5mm C		1/1.8"	1/2"	1/3"
FOCAL LENGTH		f=4.5mm		
MAX. DIAMETER (RATIO)		F=1:1.4~16		
PICTURE SIZE		5.4x7.2mm	4.8x6.4mm	3.6x4.8mm
ANGLE	VER. ANGLE	66.9°	59.4°	45.1°
	HOR. ANGLE	88.8°	79.0°	59.4°
	DIA. ANGLE	110.2°	98.4°	74.3°
DISTORTION (TV)		-17.5%		
SHOOTING RANGE AT MINIMUM FOCUS DISTANCE	VER.	273.8mm	237.1mm	170.7mm
	HOR.	405.3mm	342.1mm	237.1mm
	DIA.	592.3mm	478.7mm	313.6mm
MINIMUM FOCUS DISTANCE		0.2m		
FLANGE BACK		17.526mm in air		
BACK FOCUS		10.0mm in air		
FILTER SCREW SIZE		-----		
FRONT/REAR EFFECTIVE DIA.		FRONT ϕ 15.1mm		REAR ϕ 10.1mm
MOUNT		C-MOUNT		
EXIT PUPIL		-49.2mm		
TEMPERATURE RANGE		-10~+50°C		
STORAGE TEMPERATURE RANGE		-20~+60°C		
RESOLUTION CENTER/CORNER		CENTER 100lp/mm		CORNER 40lp/mm
WEIGHT		55 g		

NOTE: Specifications and availability are subject to change without notice
 注) 本仕様については、予告なしに変更する場合があります。



		尺度	1/1	工場番号	CG602NC
		機種名	1/1.8" F1.4 f=4.5mm		
2014.12.27	更新	機種番	LM5NCL 外観図		
2013.4.15	作成年月日				